



CRAFTED AUDIO, LLC

FOUR.2

Full-range installation loudspeaker, 4 inch cube

SPECIFICATION SHEET
REVISION A

DESCRIPTION

The Crafted FOUR.2 puts a full-range balanced mode radiator in a 4 inch cube, small enough to sit where a loudspeaker is not supposed to be visible and even enough to be the only source in the scene. Wide, consistent dispersion means placement can follow the set rather than the coverage plot.

The .2 carries the moulded body and the NHF3-dsw4 steel-basket drive unit.

FEATURES

- Moulded body — lighter and quieter to rig than the original extrusion
- NHF3-dsw4 steel-basket drive unit
- Infinitely adjustable stainless U-bracket, 1/4-20 thread
- 1/4-20 recessed nut each side, with thumb screws supplied
- Superior intelligibility and clarity at low level
- Size and flexibility allow easy retrofitting

SUPPLY

- Loudspeaker, assembled, with grille fitted
- U-bracket and mounting hardware
- Cable gland fitted to the rear — 460 mm (18 in) speaker wire pigtail

PERFORMANCE

Impedance	4 Ω
Power handling	28 W RMS
Sensitivity	89.0 dB @ 2.83 V / 1 m
Coverage	120 ° conical
Ingress protection	IP64

PHYSICAL

Width	101.6 mm (4.00 in)
Height	101.6 mm (4.00 in)
Depth, overall	124.87 mm (4.92 in)
Moulded shell	93.24 mm (3.67 in)
Grille	91.77 × 91.77 mm (3.61 × 3.61 in)
Mass	705 g (24.9 oz)

MOUNTING

Bracket	Stainless U-bracket, 16 ga
Bracket thread	1/4-20
Side fixings	2 × 1/4-20 recessed nut
Envelope	119 × 125 × 160 mm (4.7 × 4.9 × 6.3 in)

The bracket sets the acoustic axis. Aim the cube at the listener rather than squaring it to the structure — the 120° pattern gives room to trade a little aim for a tidier mount.


Crafted Audio, LLC

8051 N. Tamiami Tr. STE E6, Sarasota, FL 34243 · craftedav.com

WARRANTY — one year from date of shipment against defects in materials and workmanship. Remedy limited to repair or replacement at Crafted's option. Full terms at craftedav.com/warranty.

Balanced mode radiator technology is licensed from Tectonic. Product names of other manufacturers are used only to identify the parts described.

DOC CAV-SS-FOUR.2
REV A
ISSUED 2026-08-30



ITEM	QTY	PART NUMBER	DESCRIPTION	SUPPLY
1	1	—	Cabinet shell, injection moulded	Included
2	1	—	Front bezel, injection moulded	Included
3	1	—	Voronoi grille, magnet retained	Included, fitted
4	1	NHF3-dsw4	Drive unit, 3 inch steel basket	Included, fitted
5	1	—	U-bracket, 16 ga stainless	Included, loose
6	2	96016A233	¼-20 recessed nut — tripod thread, one each side	Included, fitted
7	2	—	¼-20 thumb screw, to suit the recessed nut	Included, loose
8	1	—	Cable gland, PG7 — rear, speaker wire pigtail	Included, fitted

1. All dimensions in millimetres. The BRACKET, TOP FACE view is 1:1 and prints as a drilling template at 100% on 11 × 17. The other three views are 1:2.
2. The loudspeaker has nothing to drill. The three holes in the bracket's top face are the mounting pattern — see BRACKET, TOP FACE.
3. The U-bracket is supplied loose and threads into the ¼-20 recessed nuts in the sides. The envelope figure allows for full rotation.
4. The speaker wire leaves the back through the gland as a 460 mm (18 in) pigtail.

Cabinet	101.57 × 101.57 × 93.24
With bezel	124.87 deep including grille
Grille	91.77 square, magnet retained
Mounting	¼-20 recessed nut each side, tripod thread
Bracket	105.11 × 94.21, 16 ga, ¼-20 thread
Envelope	118.19 × 124.91 × 159.95 with bracket
Mass	705 g

Drive unit	NHF3-dsw4, 4 Ω
Power	28 W RMS
Sensitivity	89.0 dB @ 2.83 V / 1 m
Coverage	120° conical
Connection	460 mm (18 in) speaker wire pigtail