



CRAFTED AUDIO, LLC

FOUR.2e

Network loudspeaker, 4 inch cube — PoE powered, Dante / AES67

SPECIFICATION SHEET
REVISION A

DESCRIPTION

The FOUR.2e is the FOUR.2 with the amplifier and the network interface inside it. Power and audio arrive on one Cat cable, so the only rack infrastructure a channel needs is a switch port — no amplifier, no analogue tie line, no rack space.

Mechanically identical to the FOUR.2 but for the connector, and 15 g heavier.

FEATURES

- Powered over Ethernet — one cable for audio and power
- Dante and AES67 audio transport
- 1/4-20 recessed nut each side, with thumb screws supplied
- Deliberately simple — nothing in it needs a firmware campaign

SUPPLY

- Loudspeaker, assembled, with grille fitted
- U-bracket and mounting hardware
- Two per carton

PERFORMANCE

Power	15 W AES · 30 W peak
Frequency response	170 Hz — 20 kHz
Sensitivity	91 ±3 dB
Ingress protection	IP64

NETWORK AND POWER

Connector	RJ-45, 10/100, sealed
Transport	Dante / AES67 over PoE

PHYSICAL

Width	101.6 mm (4.00 in)
Height	101.6 mm (4.00 in)
Depth, overall	124.87 mm (4.92 in)
Moulded shell	93.24 mm (3.67 in)
Grille	91.77 × 91.77 mm (3.61 × 3.61 in)
Mass	720 g (25.4 oz)

MOUNTING

Bracket	Stainless U-bracket, 16 ga
Bracket thread	1/4-20
Side fixings	2 × 1/4-20 recessed nut
Envelope	119 × 125 × 160 mm (4.7 × 4.9 × 6.3 in)

Crafted Audio, LLC

8051 N. Tamiami Tr. STE E6, Sarasota, FL 34243 · craftedav.com

WARRANTY — one year from date of shipment against defects in materials and workmanship. Remedy limited to repair or replacement at Crafted's option. Full terms at craftedav.com/warranty.

Balanced mode radiator technology is licensed from Tectonic. Product names of other manufacturers are used only to identify the parts described.

DOC CAV-SS-FOUR.2e
REV A
ISSUED 2026-08-30

